



BS656-Z22

- Platform concept with different function units
- Thermoplastic enclosure
- Wide range of alternative actuators
- Protection class IP66, IP67
- Switching point setting
- Symmetry thanks to toothed, centrally located shaft
- Central connection terminal

Data

Ordering data

Product type description	BS656-Z22
Article number (order number)	153031622
EAN (European Article Number)	4030661533100
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	TÜV cULus EAC
--------------	---------------------

General data

Standards	EN 620 EN IEC 60947-5-1
Housing material	thermosetting resin
Material of the housing cover	thermosetting resin
Gross weight	1,657 g

General data - Features

Number of auxiliary contacts	2
Number of safety contacts	2

Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	2,000,000 Operations
---	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Positionierschritte für den Betätiger	10 °

Mechanical data - Connection technique

Cable entry	2 x M25 x 1.5
Termination	Cage clamp
Cable section, minimum	0.5 mm ² , flexible

Cable section, maximum

2.5 mm², flexible

Ambient conditions

Degree of protection

IP66

IP67

Ambient temperature

-40 ... +70 °C

Protection class

II

Ambient conditions - Insulation values

Rated insulation voltage U_i

300 V

Rated impulse withstand voltage U_{imp}

4 kV

Degree of pollution

3

Electrical data

Thermal test current

6 A

Utilisation category AC-15

230 VAC

Utilisation category AC-15

3 A

Utilisation category DC-13

24 VDC

Utilisation category DC-13

3 A

Material of the contacts, electrical

Silver

Ordering code

Product type description:

BS65(1)(2)(3)(4)

(1)

215

Grey cast iron, painted

6

thermosetting resin

(2)

Z22	Snap action 2 NO contact / 2 NC contact
T22	Slow action, 2 NO contacts / 2 NC contacts
Z33	Snap action, 3 NO contacts / 3 NC contacts
T33	Slow action, 3 NO contacts / 3 NC contacts

(3)

without	without indicator lamp
G024	Indicator lamp (only for Z/T22), red (24 VDC)
G115	Indicator lamp (only for Z/T22), red (115 VAC)
G230	Indicator lamp (only for Z/T22), red (230 VAC)

(4)

without	Standard version (without Dupline® input module)
DN	With integrated Dupline® input module


Pictures

Product picture (catalogue individual photo)




ID: khds-f01
| 262.5 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi
| 22.0 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi
| 36.3 kB | .jpg | 123.472 x 82.197 mm - 350 x 233 px - 72 dpi

Dimensional drawing basic component



ID: kbs65g01
| 3.5 kB | .png | 74.083 x 44.097 mm - 210 x 125 px - 72 dpi
| 98.3 kB | .jpg | 352.778 x 209.55 mm - 1000 x 594 px - 72 dpi

Dimensional drawing basic component




ID: kbs65g02

| 71.6 kB | .jpg | 352.778 x 167.922 mm - 1000 x 476 px - 72 dpi

| 2.9 kB | .png | 74.083 x 35.278 mm - 210 x 100 px - 72 dpi

| 5.5 kB | .jpg | 89.253 x 42.686 mm - 253 x 121 px - 72 dpi

Dimensional drawing basic component



ID: kbs65g03

| 127.4 kB | .jpg | 352.778 x 195.439 mm - 1000 x 554 px - 72 dpi

| 4.7 kB | .png | 74.083 x 40.922 mm - 210 x 116 px - 72 dpi

| 11.9 kB | .jpg | 115.711 x 63.853 mm - 328 x 181 px - 72 dpi

Schmersal, Inc., 115 E Stevens Ave, Suite 208, Valhalla, NY 10595

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 09/10/2024, 12:17