

Product Nomenclature Listing

☐ **PREFIX I**

Blank - Automax manufacture

☐ **MODEL**

- 70 - PP Input 3-15 psi
- 71 - EP Input 4-20 mA General Purpose
- 72 - EP Input 4-20 mA FM/CSA/ATEX/IEC Explosionproof
- 74 - EP Input 4-20 mA FM/CSA/ATEX/IEC Intrinsically Safe
- 75 - EP Input 4-20 mA Signal Loss Fail-in-Place
- 76 - PP Input 6-30 psi

☐ **INDICATION**

- 1 - Standard Flat with Green Indicator
- 2 - UltraDome Indicator

☐ **GAUGES**

- 3 - No Gauges
- 4 - Standard Gauges (SST casing w/ brass internals)
- 5 - Stainless Steel Gauges

☐ **SPOOL VALVES**

- 6 - Low Flow Spool Valve
- 7 - High Flow Spool Valve

☐ **CAM TYPE**

- A - Standard Linear Cam 3-15 psi, 3-9 psi, 9-15 psi, D or R, 180 Degree
- B - 30 or 60 Degree Linear Cam D or R
- C - Characterized Cam Square or Square Root, D or R

☐ **OPTIONS**

- P - NAMUR Shaft - Viton Seals for 32 to 300 Degree F service (TBD)
- R - NAMUR Shaft - Tufam R66 Severe Service Coating
- T - NAMUR Shaft - Standard Epoxy Coating
- Q - NAMUR Shaft - Silicone Seals for -40 to 185 Degree F

☐ **FEEDBACK OPTIONS**

- 0 - None
- T - Top-Mounted UltraSwitch Cover

Notes: